

241 LED Multicolor Beacon MC35

Technical information	
Dimensions (ø x H)	38 mm x 33 mm (ball in)
Housing	PC, black
Lens	PC, transparent
Mounting	Installation mounting M22
Life duration light	Up to 50,000 h
Life duration buzzer	Up to 50,000 h
Operating temperature min./max.	-25°C / +55°C



QUICK FINDER MC35		MC 35 Installation mounting M22			
Protection rating	Acoustics	MC35 Standard		MC35 IO-Link	
		IP 65/68		IP 65/68	
Sound output	with buzzer	BS dB (A)	without buzzer	with buzzer	without buzzer
				BS dB (A)	
Tone types	Permanent tone	Tricolor (RGV)	without buzzer	Multitones*	
Color options	Multicolor (RGB)	Multicolor (RGB)	Multicolor (RGV)	Multicolor	Multicolor
				(>1 million colors)	(>1 million colors)
Light effect	Permanent light	24 V DC	Permanent light	Permanent, flashing, flashing, pulse light	
Voltage	24 V DC	10-30 V DC	10-30 V DC	10-30 V DC	
Connection	M 12 5-pin	M 12 5-pin			
Order no.	241 440 95	241 420 95	241 320 95	241 810 01	241 810 00

* 11 tones software-controlled

WERMA Signaltechnik GmbH + Co. KG
Dachauerstr. 15
D-78604 Bielefeld-Mellheim
Phone +49 724 9537-0
www.werma.com | info@werma.com

WERMA Signaltechnik
Werma Signaltechnik GmbH
Reinholdstraße 50
622 Neuhäusen am Rheindell
Stollberg
Phone +49 64 694 00-60
Fax +49 62 674 00-65
www.werma.com | info@werma.ch

WERMA Italia S.r.l.
Via dell'Industria 42
25122 Piacenza
Italy
Phone +39 523 044 514
www.werma.com | info@werma.it

WERMA SARL
55 Rue Calère
55780 Mors
France
Phone +33 4 7222 3737
www.werma.com | info@werma.fr

WERMA BENELUX
Postdreef 101-4C
3446 Zandvoort-Western
The Netherlands
Phone +31 9 220 311
www.werma.com | info@werma.nl

WERMA (UK) Ltd.
13 Brooklands Court
Keston, Middlesex TW9 1EX
Great Britain
Phone +44 1838 48 69 30
www.werma.com | ukinfo@werma.co.uk

WERMA USA Inc.
20000 E. Main Street, Suite A
Nacogdoches, TX 75701, USA
Phone +1 409 361 0800
www.werma.com | usinfo@werma.com

WERMA (Shanghai) Co., Ltd.
Jiading Road, No. 85, Jiading District
Songjiang Shanghai P.R.C. 201815
China
Phone +86 213774-3022
www.werma.com | info@werma.cn



LED Multicolor Beacon MC55/MC35

Moseley High / with and without buzer /



MC55 High / with and without buzzer

[illegible]

Output

MC55 Touch Smart - Configuration software



MC55 Standard / with and without buzzer /
various mounting options



MC55 High / with and without buzzer /
various mounting options



MC55 Touch / with and without buzzer /
flush mounting



MC55 Touch Smart - Configuration software



MC55 Smart - Configuration software

APPLICATION & USE

The MC series is av-

- > MC35 has a diameter of 35 mm
- > MC55 has a diameter of 55 mm and is available for floor mounting.
- > MC55 Touch has a diameter of 55 mm and is available for flush mounting.
- > MC55 High has a diameter of 55 mm and is available for flush mounting.

MC55 Touch & MC

The MC55 series str...

Typical application

- > **Acknowledgement**
Visual and auditory feedback acknowledges the user's actions
- > **Start/stop of motion**
A tap of the finger
- > **Control of peripheral devices**
Up to 200 mA can be used for additional devices
- > **Time-based escape**
In the event of motion, a visual signal (flashing) is defined and can be used

Smart – the config

The Smart version of

- > **Freely adjustable** and tones
- > **Choice of pulse :**
- > **Individual adjust**